

EV200



Indoor Unit



Specifications

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 100-200 CFM				
Unit may be mounted in any orientation				
Number Motors: One double-shaft motor				
V	HZ	Phase	Input Watts	FLA
120	60	Single	157 @ 181 CFM	1.5
Control: On board 24 VAC transformer/relay package with switched dry contacts				
Filters: MERV 8, spun polyester media. 10-1/2" x 21-3/4" x 1"				
Weight: 70 lbs (unit), 82 lbs (in carton), 125 lbs (on pallet)				
Shipping Dimensions: 32"L x 21-1/2"W x 29"H (in carton) 44" L x 34" W x 34" H (on pallet)				
Controls: PTL – Percentage Timer Control FM – Percentage Timer Control with Furnace Interlock PBL – Push Button Point-of-Use Controls				
Accessories: Wall Caps Back Draft Dampers				

G5 Performance

Airflow CFM	ESP in H ₂ O	Temp EFF%	Total EFF% Winter/Summer*
122	0.70	81	77/64
149	0.60	79	75/61
168	0.50	78	73/59
176	0.40	78	72/59
186	0.30	77	72/58
192	0.20	77	71/57
207	0.10	76	70/56

* (See HVI certification report on page 11 for complete certified rating).

Dimensions

